



150W




Smart LED Lighting

LED Retrofit Kits

Suitable for Outdoor Pole/Arm-Mounted Area and Roadway Luminaires.

Features & Benefits:

- Built-in Surge Suppressors & Transient Protection
- High Power Factor UL Listed LED Driver
- 5-Years / 50,000 Hours (*) Warranty
- Bright • High CRI
- Low THD



Model	Product	Size	Power	Flux	Equivalent
LRK-150W-57KC	150W 5,700K LED Retrofit Kit	LED Engine (L) 10 ³ / ₈ " (W) 6 ¹ / ₄ " (D) 2 ³ / ₈ "	150W	16,800 Lumen	600W MH or HPS

• Rated Voltage: 120-277Vac ~50/60Hz • P.F. > 0.9 • >100lm/W • CRI ≈ 70 •
 •(*) Rated Life 50,000 Hrs. (L₇₀ B₅₀) at T_[A] 25°C Max. • Beam Angle 90° • Pigtail Wire/Cable LED Driver to Mains •




150W




Smart LED Lighting

LED Retrofit Kits



Light & Bright

**Size / Dimensions
LED Engine**
(L) 10³/₈" x (W) 6¹/₄"
(D) 2³/₈"



Model	Product	Power	Equivalent
LRK-150W-57KC	150W 5,700K LED Retrofit Kit	150W	600W MH &/or HPS Lamp
Input Voltage	Power/Power Factor	Efficacy	Flux
120-277Vac ~50/60Hz	155W Max. P.F. > 0.9	>100 lm/W	16,800 Lumen
Color Rendering	Color Temperature	Beam Angle	Life
CRI ≈ 70	5,700K CCT ±10%	90°	50,000 Hours (L ₇₀ B ₅₀) T _[A] 25°C Max.