

400W ~ 800W LED Stadium Flood Lights



- Directive 15° ~ 40° Beam Angle Option •
- 5-Years / 50,000 Hours Warranty^(*) •
- 7-Years Warranty UL Certified LED Driver •
- Input Voltage Range 120-277-347-480Vac •
- IP65^(#) Suitable for Damp & Wet Locations •
- Built-in Surge Protection Device 20KV/10KA •



Model	Product	Size	Power	Flux	Eqv.
SFL-400W-50K-NF-277V	LED Stadium Flood Light 400W 5000K 40° 120-277Vac	Ø 15" (H) 18"	400W	60,000 Lumens	1,000W
SFL-500W-50K-NF-277V	LED Stadium Flood Light 500W 5000K 40° 120-277Vac	Ø 15" (H) 18"	500W	75,000 Lumens	1,500W
SFL-600W-50K-NF-277V	LED Stadium Flood Light 600W 5000K 40° 120-277Vac	Ø 18" (H) 20"	600W	90,000 Lumens	1,500W
SFL-800W-50K-NF-277V	LED Stadium Flood Light 800W 5000K 40° 120-277Vac	Ø 18" (H) 20"	800W	120,000 Lumens	2,000W

- "277V" for 120-277Vac or "480V" for 208-480Vac ~50/60Hz • P.F. > 0.95 • ~150lm/W • CRI ≈ 80 • Cable & J-Box Connection •
- (*) Rated Life 50,000 Hrs. (L₇₀ B₅₀) at T_[A] 25°C Max. • (#) IP65 ≈ Equal to NEMA Enclosure Rating 4 •
- "SF" Sharp Flood 15°, "NF" Narrow Flood 40° • "Eqv." ÷ Comparable Equivalence to Metal Halide Lamps Wattage •