



4 ft. T5 LED Tubes

Direct Wire Internal Driver (UL Type B)

Features & Benefits:

- T5 & T5HO Fluorescent Tube Replacements
- 5-Years / 50,000 Hours Warranty (*)
- Low Energy, High Lumen per Watt
- Low Temp. Instant Start
- Flicker Free Lighting
- Shatter Proof Design



Model	Product	Size	Power	Flux	Equivalent
F54T5F-20W-30K-DL	T5 LED Tube 4ft. 20W 3000K Frosted	4ft. (1149mm)	20W	2,200 lm	F54T5 54W 4ft HO FL Tube
F54T5F-20W-40K-DL	T5 LED Tube 4ft. 20W 4000K Frosted		20W	2,500 lm	F54T5 54W 4ft HO FL Tube
F54T5F-20W-50K-DL	T5 LED Tube 4ft. 20W 5000K Frosted		20W	2,500 lm	F54T5 54W 4ft HO FL Tube

- 120~277Vac ~50/60Hz • P.F. > 0.95 • Miniature Bi-pin Base (G5) • Efficacy 125lm/W •
- CCT 5500K (55K), 4000K (40K) or 3000K (30K) ±10% • CRI >80 •
- "Eqv." ÷ Comparable Equivalence to Fluorescent T5HE/T5HO Wattage •