



Metal Halide & High Pressure Sodium 250W LED Replacement Lamp

- High Power Factor • Self Ballasted •
- Suitable for Open & Enclosed Fixtures •
- Bright • High CRI • High Lumen Output •
- Built-in 20KV/10KA Surge Protection (SPD) •
- 5-Years / 50,000 Hours Warranty (*) •



Available in:

CCT 5,500K ±10% (CW) for MH Replacement

CCT 3,000K ±10% (WW) for HPS Replacement




- Simple Installation • High Lumen per Watt • Rugged Design •

Model	Product	Size	Power	Flux	Equivalent
CL-250W12-55K-E39	LED Lamp 250W 360° 55K MH Replacement	Ø5 ³ / ₈ x 12 ¹ / ₂ "	250W Max.	41,300 Lumen	1,000W MH Lamps
CL-250W12-30K-E39	LED Lamp 250W 360° 30K HPS Replacement	Ø5 ³ / ₈ x 12 ¹ / ₂ "	250W Max.	39,200 Lumen	1,000W HPS Lamps

- 120-277Vac ~50/60Hz • PF > 0.9 • Med. (E26) or Mogul (E39) Lamp Base • ~165 lm/W • CRI >75 •
- (*) Rated Life 50,000 Hrs. (L₇₀ B₅₀) at T_[A] 25°C Max. • CCT 5500K (55K) or 3000K (30K) ±10% •



250W Cluster LED Lamp



Model	Product	Power	Equivalent
CL-250W12-xxK-E39	Cluster LED Bulb	250W	1,000W MH/HPS
Input Voltage	Power/Power Factor	Efficacy	Flux
120-277Vac ~50/60Hz	250W Max. P.F. ≈ 0.97	~165 lm/W	41,300 Lumen (CW) 39,200 Lumen (WW)
Color Rendering	Color Temperature	Beam Angle	Life
CRI ÷ 75~80	30K ÷ CCT 3,000K ±10% 55K ÷ CCT 5,500K ±10%	360°	5-Years / 50,000 Hours (L ₇₀ B ₅₀) T _[A] 25°C Max.