



# 30W 4ft. (120cm) Linear Surface Mount LED Fixture

## LED Parking Garage and Passageway Luminaires

- 5-Years | 50,000 Hours Warranty<sup>(\*)</sup> •
- Built-in Surge Suppressors & Protection •
- Bright - High CRI - High Lumen Output •
- High Power Factor - Self Ballasted •



Available in CCT 3,000K – 4,000K – 5,500K ±10%

- Simple Installation • High Lumen per Watt • Rugged Design •

Model	Product	Size	Power	Flux	Equivalent
WML-4FT-30W-30K	Wall Mount LED Fixture 4ft (120CM) 30W 3000K	(L) 48" (W) 2" (H) 2"	30W	3,700 Lumen	4 x F17T8/12 (2ft. 17W ea.)
WML-4FT-30W-40K	Wall Mount LED Fixture 4ft (120CM) 30W 4000K	(L) 122cm (W) 5cm (H) 5cm	30W	3,900 Lumen	2 x F32T8/12 (4ft. 32W ea.)
WML-4FT-30W-55K	Wall Mount LED Fixture 4ft (120CM) 30W 5500K		30W	3,900 Lumen	2 x FB32T8/12 (U-Bent 32W ea.)

- (\*) Rated Life > 50,000 Hrs. (L<sub>70</sub> B<sub>50</sub>) at T<sub>[A]</sub> 25°C Max. •
  - 120-277Vac ~50/60Hz • Pigtail Wire/Cable • P.F. > 0.9 • THD < 20% •
  - CCT 5500K (55K), 4000K (40K), 3000K (30K) ±10% • 130 lm/W • CRI ≈ 80 •
- "Equivalent" ÷ Comparable Equivalence to T8/T12 Florescent Tubes