



Modular Wall Wash LED Fixture

**200W LED Luminaires for
Commercial & Industrial Buildings
IP65 Dust & Water Proof**



Features & Benefits:

- Great Energy Savings !
- Directive NF/MF/WF Beam Angle
- 5-Years | 50,000 Hours Warranty^(*)
- High Power Factor – UL Listed Driver
- Bright – High CRI – High Lumen Output
- Built-in Surge Suppressors & Protection
- CCT 5500K, 4000K, 3000K for MH & HPS Replacement



40° / 90° / 150°x80° Beam Angle available on request

IP65 ≈ NEMA Enclosure Rating 4



| Model | Product | Size | Power | Flux | Equivalent |
|----------------------|---|--|-------------|-----------------|-------------------|
| MFL-200W-55K-WF-277V | Modular Wall Wash LED Fixture 200W 5500K 150°x80° 277Vac | (L) 17 ⁵ / ₈ " (W) 12" (H) 3 ¹ / ₄ " | 200W Max | 30,000 Lumen | 1,000W MH Lamp |
| MFL-200W-55K-WF-480V | Modular Wall Wash LED Fixture 200W 5500K 150°x80° 480Vac | | 200W Max | 30,000 Lumen | 1,000W MH Lamp |

- "277V": 120-277Vac or "480V": 208-480Vac ~50/60Hz • P.F. > 0.9 • 3ft. Cable/Loose Leads Wires • THD <20% •
- CCT 5500K (55K), 4000K (40K), 3000K (30K) ±10% • CRI > 70 • ~150 lm/W •
- "NF" Narrow Flood 40°, "MF" Medium Flood 90°, "WF" Wide Flood 150°x80° •
- (*) Rated Life 50,000 Hrs. (L₇₀ B₅₀) at T_[A] 25°C Max. •
- "Equivalent" ÷ Comparable Equivalence to Metal Halide (MH) Lamp & Fixtures