



# T5 LED Tubes

## Ballast Compatible Internal Driver (UL Type A)

### Features & Benefits:

- Flicker Free Lighting
- Shatter Proof Design
- Low Temp. Instant Start
- Color Temp. 3000K, 4000K, 5000K
- Low Energy, High Lumen per Watt
- 5-Years / 50,000 Hours Warranty (★)
- Auto Ballast Compatible, Standard & HO
- T5 & T5HO Fluorescent Tube Replacements



Model	Product	Size	Power	Flux	Equivalent
F24T5F-12W-40K-DBC	T5 LED Tube 2ft. 12W 4000K Frosted	2ft. (549mm)	12W	1,500 lm	F24T5 24W 2ft HO FL Tube
F24T5F-16W-40K-DBC	T5 LED Tube 2ft. 16W 4000K Frosted	3ft. (849mm)	16W	2,000 lm	F39T5 24W 3ft HO FL Tube

- 120~277Vac ~50/60Hz • P.F. > 0.95 • Miniature Bi-pin Base (G5) • Efficacy 125lm/W •
- CCT 5500K (55K), 4000K (40K) or 3000K (30K) ±10% • CRI >80 •
- "Eqv." ÷ Comparable Equivalence to Fluorescent T5HE/T5HO Wattage •