



4 ft. T5 LED Tubes

Ballast Compatible Internal Driver (UL Type A)

Features & Benefits:

- Flicker Free Lighting
- Shatter Proof Design
- Low Temp. Instant Start
- Low Energy, High Lumen per Watt
- 5-Years / 50,000 Hours Warranty (*)
- Auto Ballast Compatible, Standard & HO
- T5 & T5HO Fluorescent Tube Replacements



Model	Product	Size	Power	Flux	Equivalent
F54T5F-14W-30K-DBC	T5 LED Tube 4ft. 14W 3000K Frosted	4ft. (1219 mm)	14W	1,750 lm	F54T5 28W 4ft FL Tube
F54T5F-25W-30K-DBC	T5 LED Tube 4ft. 25W 3000K Frosted		25W	3,125 lm	F54T5 54W 4ft HO FL Tube
F54T5F-14W-40K-DBC	T5 LED Tube 4ft. 14W 4000K Frosted		14W	1,750 lm	F54T5 28W 4ft FL Tube
F54T5F-25W-40K-DBC	T5 LED Tube 4ft. 25W 4000K Frosted		25W	3,125 lm	F54T5 54W 4ft HO FL Tube
F54T5F-14W-50K-DBC	T5 LED Tube 4ft. 14W 5000K Frosted		14W	1,750 lm	F54T5 28W 4ft FL Tube
F54T5F-25W-50K-DBC	T5 LED Tube 4ft. 25W 5000K Frosted		25W	3,125 lm	F54T5 54W 4ft HO FL Tube

- 120~277Vac ~50/60Hz • P.F. > 0.95 • Miniature Bi-pin Base (G5) • Efficacy 125lm/W •
- CCT 5500K (55K), 4000K (40K) or 3000K (30K) ±10% • CRI >80 •
- "Eqv." ÷ Comparable Equivalence to Fluorescent T5HE/T5HO Wattage •