



72W 8ft. Linear Surface Mount LED Fixture

LED Stairwell and Passageway Luminaires

- Dimmable •
- Rated Life 50,000 Hours (*) •
- High Power Factor • Self Ballasted •
- Bright • High CRI • High Lumen Output •
- Built-in Surge Suppressors & Protection •



Available in CCT 3,000K – 4,000K – 5,500K ±10%

- Simple Installation • High Lumen per Watt • Rugged Design •

Model	Product	Size	Power	Flux	Equivalent
WML-8FT-72W-30K	Wall Mount LED Fixture 8ft 72W 3000K	(L) 96" (W) 2" (H) 2"	72W	9,000 Lumen	4 x F32T8/12 (4ft. 32W ea.)
WML-8FT-72W-40K	Wall Mount LED Fixture 8ft 72W 4000K		72W	9,400 Lumen	2 x F96T8/12 (8ft. 59W ea.)
WML-8FT-72W-55K	Wall Mount LED Fixture 8ft 72W 5500K		72W	9,600 Lumen	

- 120-277Vac ~50/60Hz • Pigtail Wire/Cable • P.F. > 0.9 • ~130 lm/W • CRI ≈ 80 •

- (*) Rated Life > 50,000 Hrs. (L₇₀ B₅₀) at T_[A] 25°C Max. •

- CCT 5500K (55K), 4000K (40K), 3000K (30K) ±10% •

"Equivalent" ÷ Comparable Equivalence to T8/T12 Florescent Tubes