



Smart LED Lighting



# 2 ft. LED Tubes

## U Bend Fluorescent Replacements Dual Mode Internal Driver (UL Type A + B)

### Features & Benefits:

- Flicker Free Lighting •
- Shatter Proof Design •
- Low Temp. Instant Start •
- Low Energy, High Lumen per Watt •
- No Ballast for Cost & Power Saving •
- Available in Color Temp. 3000K, 4000K, 5500K •



Model	Product	Size	Power	Flux	Equivalent
FB32T8-15W-55K-DBD	T8 LED Tube 2 FT. 15W, 5500K , U Bent 6" CTC	2 FT. 6" CTC	15W	1,950 lm	FBT8 32W
FB32T8-15W-40K-DBD	T8 LED Tube 2 FT. 15W, 4000K , U Bent 6" CTC	2 FT. 6" CTC	15W	1,950 lm	FBT8 32W
FB32T8-15W-30K-DBD	T8 LED Tube 2 FT. 15W, 3000K , U Bent 6" CTC	2 FT. 6" CTC	15W	1,800 lm	FBT8 32W

- 100~277Vac ~50/60Hz • P.F. > 0.95 • Medium Bi-pin Base (G13) • Efficacy >130lm/W •
- CCT 5500K (55K), 4000K (40K) or 3000K (30K) ±10% • CRI >80 •
- "Eqv." ÷ Comparable Equivalence to Fluorescent T8/T12 Wattage •