



Smart LED Lighting



2x4' Backlit LED Panel

Color & Power Adjustable

Luminaires for Ambient Lighting of Interior Commercial Spaces

- 0-10V Dimmable LED Driver •
- High Power Factor • Self Ballasted •
- 5-Years | 50,000 Hours Warranty (*) •
- Bright • High CRI • High Lumen Output •
- Power Adjustable 30W-40W-50W-60W-72W •
- CCT Adjustable 30K-35K-40K-50K-65K •



Model	Product	Power	Flux	Equal
T-BAR-2x4FT-72WD-30K-3065K-CPA	2x4' Backlit LED Panel 0-10V DIM 120~277V	30W	3,900	4 x F32T8 (4ft. 32W) 4 x F54T5 (4ft. 54W)
DLC PREMIUM QPL ID: S-PD2N4G	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces	40W	5,200	
Manufacture: OLYMPIA		50W	6,500	
		60W	7,800	
		72W	9,360	
		0-10V Dimmable	Lumens	

- 120-277Vac ~50/60Hz • Junction Box / Terminals • P.F. > 0.9 • THD < 20% •
- (*) Rated Life 50,000 Hrs. (L₇₀ B₅₀) at T_[A] 25°C Max. • 130 Lm/W • CRI > 80 •
- CCT Selectable: 3000K – 3500K – 4000K – 5000K – 6500K ±10% •





Smart LED Lighting



2x4' LED Panel

CCT & PWR Adjustable



Size / Dimensions
L = 48" (126cm)
W = 24" (61cm)
T = 1 5/8" (4cm)



Model	Product	Power	Equivalent
T-BAR-2x4FT-72WD-30K-3065K-CPA	2x4' Backlit LED Panel CCT + PWR ADJ. & DIM	30W ~ 72W 0-10V DIM	T8/T12 & T5/T5HO FL Tube
Input Voltage	Power Factor	Efficacy	Flux
120-277Vac ~50/60Hz	P.F. ≈ 0.9	130 Lm/W	3,900 ~ 9,360 Lumens
Color Rendering	Color Temperature	Beam Angle	Life
CRI > 80	3000K – 3500K – 4000K – 5000K – 6500K ±10%	120°	5-Years / 50,000 Hrs (L ₇₀ B ₅₀) T _[A] 25°C Max.