



Smart LED Lighting

75W Post Top LED Area Luminaire

Outdoor Pole/Arm-Mounted Area and Roadway Luminaire

Features & Benefits:

- Great Energy Savings ! •
- Directive 90° Beam Angle •
- 5-Years | 50,000 Hours Warranty (*) •
- High Power Factor – UL Listed Driver •
- Bright – High CRI – High Lumen Output •
- Built-in Surge Suppressors & Protection •
- CCT 5,000K ideal for MH Lamps Replacement •






Model	Product	Size	Power	Flux	Equivalent
ALF-75W-50K-277V	Post Top LED Area Light 75W 5000K 277V	(H) 25¾" (Ø) 17¾"	75W	9,750 lm	320W MH
ALF-75W-50K-480V	Post Top LED Area Light 75W 5000K 480V	(H) 25¾" (Ø) 17¾"	75W	9,750 lm	320W MH

- "277V" 120-277Vac | | "480V" 208-480Vac ~50/60Hz • P.F. > 0.9 • THD < 20% • Terminal Block •
- Color Temp. (CCT) 5000K ±10% • 130 Lumen per Watt • CRI ≈ 70 •
- Post Top Mount: O.D. 2⅜" (Standard) or O.D. 3" (Optional) • EPA 1.2 •
- (*) Rated Life 50,000 Hrs. (L₇₀ B₅₀) at T_A 25°C Max. •



Smart LED Lighting

75W Post Top LED Area Luminaire



Model	Product	Power	Equivalent
ALF-75W-50K-277V ALF-75W-50K-480V	Post Top LED Area Light 75W 5000K	75W	320W MH
Input Voltage	Power Factor	Efficacy	Flux
"277V": 120-277Vac "480V": 208-480Vac	P.F. ≈ 0.9 ~50/60Hz	130 lm/W	9,500 Lumen
Color Rendering	Color Temperature	Beam Angle	Life
CRI ÷ 70	CCT 5000K ±10%	90°	5-Years / 50,000 Hrs (L ₇₀ B ₅₀) T _A 25°C.



Smart LED Lighting



75W Post Top LED Area Luminaire

Assembly Drawings

