



Smart LED Lighting

Metal Halide & High Pressure Sodium 350W

LED Replacement Lamp

External LED Driver

ETL Certified for Compliance

to UL1598C and UL1993

• UL Listed LED Driver •

• High Power Factor • Low THD •

• 5-Years / 50,000 Hours Warranty (*) •

• Suitable for Open & Enclosed Fixtures •

• Bright • High CRI • High Lumen Output •

• Built-in Surge Suppressors & Protection •



U.S. Pat. D819,839



Available in:

CCT 5,500K $\pm 10\%$ (CW) for MH Replacement

CCT 3,000K $\pm 10\%$ (WW) for HPS Replacement

• Simple Installation • High Lumen per Watt • Rugged Design •

• UL Listed External LED Driver [0~10V Dimmable On-Request] • Ballast By-Pass UL Type C •

Model	Product	Size	Power	Flux	Equivalent
CL -350W12X-55K-E39	LED Lamp 350W 360° 55K MH Replacement	$\varnothing 5\frac{3}{8}$ x L=12 $\frac{3}{4}$ "	350W Max.	63,000 Lumen	1,000W MH Lamps
CL-350W12X-55K-E39LN (Long Neck)	LED Lamp 350W 360° 55K MH Replacement	$\varnothing 5\frac{3}{8}$ x L=14 $\frac{3}{8}$ "	350W Max.	63,000 Lumen	1,000W MH Lamps
CL-350W12XH-55K-E39 (480Vac)	LED Lamp 350W 360° 55K MH Replacement	$\varnothing 5\frac{3}{8}$ x L=12 $\frac{3}{4}$ "	350W Max.	63,000 Lumen	1,000W MH Lamps
CL-350W12XH-55K-E39LN (480Vac Long Neck)	LED Lamp 350W 360° 55K MH Replacement	$\varnothing 5\frac{3}{8}$ x L=14 $\frac{3}{8}$ "	350W Max.	63,000 Lumen	1,000W MH Lamps

• 120-277Vac | "H": 208-480Vac ~50/60Hz • PF > 0.9 • THD < 20% • Mogul (E39) Lamp Base •






• "X" External Driver • (*) Rated Life 50,000 Hrs. (L₇₀ B₅₀) at T_A 25°C Max. • CCT 3000(30K) or 5500K (55K) $\pm 10\%$ •

• CRI ~85 • ~180 lm/W •



Smart LED Lighting

350W Cluster LED Lamp



Item	Model	Power	Equivalent
CL-350W12X-ccK-E39nn	Cluster LED Bulb	350W	1,000W MH/HPS
Input Voltage	Power/Power Factor	Efficacy	Flux
120-277Vac H: 208-480Vac	350W Max. P.F. ≈ 0.98	~180 lm/W	63,000 Lumen
Color Rendering	Color Temperature	Beam Angle	Life
CRI ÷ 85	30K ÷ CCT 3,000 ±10% 55K ÷ CCT 5,500K ±10%	360°	5-Years / 50,000 Hours (L ₇₀ B ₅₀) T _[A] 25°C Max.