



Smart LED Lighting



## 2 ft. 8W T8 LED Tubes

### T8 & T12 Fluorescent Replacements

#### Dual Mode Internal Driver (UL Type A + B)

##### Features & Benefits:

- Flicker Free Lighting •
- Low Temp. Instant Start •
- Shatter Proof, PC+Alum. Design •
- Color Temp. 3000K, 4000K, 5000K •
- Ballast Compatible or Direct Wire •
- Low Energy, High Lumen per Watt •
- 5-Years | 50,000 Hours Warranty (\*) •



| Model             | Product                             | Size                    | Power      | Flux           | Equivalent   |
|-------------------|-------------------------------------|-------------------------|------------|----------------|--------------|
| F16T8D-8W-30K-DBD | T8 LED Tube 2ft<br>8W 3000K Frosted | 2ft. T8<br>Ø 1" x L 24" | 8W<br>Typ. | 1,070<br>Lumen | F17T8<br>17W |
| F16T8D-8W-40K-DBD | T8 LED Tube 2ft<br>8W 4000K Frosted | 2ft. T8<br>Ø 1" x L 24" | 8W<br>Typ. | 1,070<br>Lumen | F17T8<br>17W |
| F16T8D-8W-50K-DBD | T8 LED Tube 2ft<br>8W 5000K Frosted | 2ft. T8<br>Ø 1" x L 24" | 8W<br>Typ. | 1,070<br>Lumen | F17T8<br>17W |

- 120~277Vac ~50/60Hz • P.F. > 0.9 • THD <20% • Medium Bi-pin Base (G13) • Efficacy >130lm/W • CRI >80 •
- (\*) Rated Life > 50,000 Hrs. (L<sub>70</sub> B<sub>50</sub>) at T<sub>A</sub> 45°C Max. • CCT 5000K (50K), 4000K (40K) or 3000K (30K) ±10% •
- "Equivalent." ÷ Comparable Equivalence to Fluorescent T8/T12 Wattage •