



Smart LED Lighting



250W Hi-Bay LED Fixture

LED High-Bay Luminaires for
Commercial & Industrial Buildings

IP65 Dust & Water Proof



Features & Benefits:

- Great Energy Savings ! •
- Directive 60°/90° Beam Angle •
- 5-Years | 50,000 Hours Warranty (*) •
- High Power Factor – UL Listed Driver •
- Bright – High CRI – High Lumen Output •
- Built-in Surge Suppressors & Protection •
- CCT 5,500K ideal for MH Lamps Replacement •



45°/60°/90°/120° Beam Angle
available on request

IP65 ≈ NEMA Enclosure Rating 4





Model	Product	Size	Power	Flux	Equivalent
HBF-250W-55K-60d-277V	250W High Bay LED Fixture 5,500K 60° 120-277Vac	(dia.) 14¼" x (H) 6"	250W Max	38,750 Lumen	1,000W MH Lamp
HBF-250W-55K-90d-277V	250W High Bay LED Fixture 5,500K 90° 120-277Vac		250W Max	38,750 Lumen	1,000W MH Lamp
HBF-250W-55K-60d-480V	250W High Bay LED Fixture 5,500K 60° 208-480Vac		250W Max	38,750 Lumen	1,000W MH Lamp
HBF-250W-55K-90d-480V	250W High Bay LED Fixture 5,500K 90° 208-480Vac		250W Max	38,750 Lumen	1,000W MH Lamp

- 120-277Vac or 208-480Vac ~50/60Hz • P.F. > 0.9 • Chain Hook + 6ft. Cable/Loose Leads Wires • THD <20% •
- (*) Rated Life 50,000 Hrs. (L₇₀ B₅₀) at T_A 25°C Max. • CCT 5500K (55K) ±10% • CRI > 70 • ~155 lm/W •
- "Equivalent" ÷ Comparable Equivalence to Metal Halide (MH) Lamp & Fixtures





Smart LED Lighting

250W Hi-Bay LED Fixture



Size / Dimensions
Ø 14¼" (dia.)
H 6" (Hight)



Model	Product	Power	Equivalent
HBF-250W-55K-60d-277V HBF-250W-55K-90d-277V	Hi-Bay LED Fixture 250W CCT 5500K	250W	1,000W MH Lamp High-Bay Light Fixture
Input Voltage	Power/Power Factor	Efficacy	Flux
"277V": 120-277Vac ~50/60Hz "480V": 208-480Vac ~50/60Hz	250W Max. P.F. ≈ 0.97	~155 lm/W	38,750 Lumen
Color Rendering	Color Temperature	Beam Angle	Life
CRI ÷ 75~80	CCT 5500K ±10%	"60d": 60° "90d": 90°	50,000 Hours (L ₇₀ B ₅₀) T _A 25°C Max.