



**Smart LED Lighting** 

## Modular Wall Wash LED Fixture

Powered by PHILIPS
LUMILEDS

**200W LED Luminaires for** 

**Commercial & Industrial Buildings** 

**IP65 Dust & Water Proof** 

## **Features & Benefits:**

- Great Energy Savings! •
- Directive NF/MF/WF Beam Angle
- 5-Years | 50,000 Hours Warranty(\*) •
- High Power Factor UL Listed Driver
- Bright High CRI High Lumen Output •
- Built-in Surge Suppressors & Protection
- CCT 5500K, 4000K, 3000K for MH & HPS Replacement

40° / 90° / 150°x80° Beam Angle available on request















Model	Product	Size	Power	Flux	Equivalent
MFL-200W-30K-NF-277V	Modular Wall Wash LED Fixture	(L) 17%"	200W	30,000	1,000W
MFL-200W-30K-NF-480V	200W 3000K 40° 277/480V		Max	Lumen	MH Lamp
MFL-200W-40K-NF-277V MFL-200W-40K-NF-480V	Modular Wall Wash LED Fixture 200W 4000K 40° 277/480V	(W) 12"	200W Max	30,000 Lumen	1,000W MH Lamp
MFL-200W-55K-NF-277V	Modular Wall Wash LED Fixture	(H) 3¼"	200W	30,000	1,000W
MFL-200W-55K-NF- <mark>480V</mark>	200W 5500K 40° 277/480V		Max	Lumen	MH Lamp

- "277V": 120-277Vac or "480V": 208-480Vac ~50/60Hz P.F. > 0.9 3ft. Cable/Loose Leads Wires THD <20% CCT 5500K (55K), 4000K (40K), 3000K (30K) ±10% CRI > 70 ~150 lm/W
  - "NF" Narrow Flood 40°, "MF" Medium Flood 90°, "WF" Wide Flood 150°x80°
    - (\*) Rated Life 50,000 Hrs. (L<sub>70</sub> B<sub>50</sub>) at T<sub>[A]</sub> 25°C Max. •

"Equivalent" ÷ Comparable Equivalence to Metal Halide (MH) Lamp & Fixtures