



Smart LED Lighting



1x4' Backlit LED Panel

Color & Power Adjustable

Luminaires for Ambient Lighting of Interior Commercial Spaces

- 0-10V Dimmable LED Driver •
- High Power Factor • Self Ballasted •
- 5-Years | 50,000 Hours Warranty (*) •
- CCT Adjustable 30K-40K-50K-57K-65K •
- Bright • High CRI • High Lumen Output •
- Power Adjustable 30W-35W-40W-45W-50W •



Model	Product	Power	Flux	Equal
T-BAR-1x4FT-50WD-3065K-CPA	1x4' Backlit LED Panel 0-10V DIM 120~277V	30W 35W 40W 45W 50W 0-10V Dimmable	3,750 4,375 5,000 5,625 6,250 Lumens	4 x F17T8 (2ft. 17W) 2 x F32T8 (4ft. 32W) 2 x FB32T8 (U-Bent 32W)
DLC PREMIUM QPL ID: S-9N1Z19	1x4 Luminaires for Ambient Lighting of Interior Commercial Spaces			
Manufacture: OLYMPIA				

- 120-277Vac ~50/60Hz • Junction Box / Terminals • P.F. > 0.9 • THD < 20% •
- (*) Rated Life 50,000 Hrs. (L₇₀ B₅₀) at T_A 25°C Max. • 125 Lm/W • CRI > 80 •
- CCT Selectable: 3000K – 4000K – 5000K – 5700K - 6500K ±10% •





Smart LED Lighting




1x4' LED Panel

CCT & PWR Adjustable



Size / Dimensions
L = 48" (126cm)
W = 24" (61cm)
T = 1⁵/₈" (4cm)



Model	Product	Power	Equivalent
T-BAR-1x4FT-50WD-3065K-CPA	1x4' Backlit LED Panel CCT + PWR ADJ. & DIM	30W ~ 50W 0-10V DIM	T8/T12 & U-Bent Tube
Input Voltage	Power Factor	Efficacy	Flux
120-277Vac ~50/60Hz	P.F. $\approx$ 0.9	125 Lm/W	3,750 ~ 6,250 Lumens
Color Rendering	Color Temperature	Beam Angle	Life
CRI > 80	3000K – 4000K – 5000K – 5700K – 6500K $\pm$ 10%	120°	5-Years / 50,000 Hrs (L ₇₀ B ₅₀) T _[A] 25°C Max.