



Smart LED Lighting



30W 4ft. (120cm) Linear Surface Mount LED Fixture

LED Parking Garage and Passageway Luminaires

- High Power Factor - Self Ballasted •
- 5-Years | 50,000 Hours Warranty(★) •
- Bright - High CRI - High Lumen Output •
- Built-in Surge Suppressors & Protection •



Available in CCT 3,000K – 4,000K – 5,500K ±10%

- Simple Installation • High Lumen per Watt • Rugged Design •

Model	Product	Size	Power	Flux	Equivalent
VPL-4FT-30W-30K	Wall Mount LED Fixture 4ft (120CM) 30W 3000K	(L) 48" (W) 2" (H) 2"	30W	3,700 Lumen	4 x F17T8/12 (2ft. 17W ea.)
VPL-4FT-30W-40K	Wall Mount LED Fixture 4ft (120CM) 30W 4000K		30W	3,900 Lumen	2 x F32T8/12 (4ft. 32W ea.)
VPL-4FT-30W-55K	Wall Mount LED Fixture 4ft (120CM) 30W 5500K	(L) 122cm (W) 5cm (H) 5cm	30W	3,900 Lumen	2 x FB32T8/12 (U-Bent 32W ea.)

- (★) Rated Life > 50,000 Hrs. (L_{70} B_{50}) at $T_{[A]}$ 25°C Max. •
- 120-277Vac ~50/60Hz • Pigtail Wire/Cable • P.F. > 0.9 • THD < 20% •
- CCT 5500K (55K), 4000K (40K), 3000K (30K) ±10% • 130 lm/W • CRI ≈ 80 •
- “Equivalent” ÷ Comparable Equivalence to T8/T12 Florescent Tubes